



TECHNICAL DATA SHEET

CODE:
08C.0070CG0.00B0
Rev.08 Pg.1/1
Date 11/01/2021

REFRIGERATED COMPRESSED AIR DRYER

MODEL:

HTD 70 230/1/50

Rated capacity*

Flow rate	m ³ /h	70	
	l/min	1167	
	cfm	41,2	
Inlet air temperature	°C / °F	60 / 140	(Max 82 / 180)
Outlet air temperature	°C / °F	27 / 81	(Max 47 / 117)
Ambient temperature	°C / °F	25 / 77	(Max 45 / 113)
Working pressure	bar / psi	7,0 / 101,5	(Max 16 / 232)
Pressure drop	bar / psi	0,33 / 4,79	(Max 0,34 / 4,93)
Pressure dew point	°C / °F	7 / 45	
Power supply	V/Ph/Hz	230/1/50	(±10% / -- / ±1)
Rated power consumption	kW	0,41	(Max 0,56)
Rated adsorption	A	2,92	(Max 3,56)
Lock Rotor Ampere	A	16	
Weight	Kg / Lbs	34 / 75	
Air connections	IN/OUT	½" BSP	
Coolant type	Freon	R513A	

Standard features

Control panel:	Electronic system type	Separator type:	Demister type
Condenser cooling:	Air cooled	Compressor type:	Hermetic type
Ventilator motor:	Suction fan	Installation location:	Indoor
Heat exchanger:	Aluminium brazed plate	Drain discharge:	Timed solenoid valve
Expansion method:	Capillary tube	Electric protection:	IP 42

* Performances refer to air suction of FAD 20°C (68°F), 1 bar (14.5 psig), and the following operating conditions: 7 bar (100 psig) working pressure, 3°C (37°F) pressure dewpoint, 25°C (77°F) ambient temperature, 60°C (140°F) compressed air inlet temperature.

Performances & specifications: +/- 5%

