

## REFRIGERATED COMPRESSED AIR DRYER

### MODEL:

**ED 24 230/1/50**

Rated capacity\*

|                         |                   |             |                   |
|-------------------------|-------------------|-------------|-------------------|
| Flow rate               | m <sup>3</sup> /h | 24          |                   |
|                         | l/min             | 400         |                   |
|                         | cfm               | 14,1        |                   |
| Inlet air temperature   | °C / °F           | 35 / 95     | (Max 60 / 140)    |
| Outlet air temperature  | °C / °F           | 27 / 81     | (Max 47 / 117)    |
| Ambient temperature     | °C / °F           | 25 / 77     | (Max 50 / 122)    |
| Working pressure        | bar / psi         | 7,0 / 101,5 | (Max 16 / 232)    |
| Pressure drop           | bar / psi         | 0,04 / 0,58 | (Max 0,34 / 4,93) |
| Pressure dew point      | °C / °F           | 3 / 37      |                   |
| Power supply            | V/Ph/Hz           | 230/1/50    | (±10% / -- / ±1)  |
| Rated power consumption | kW                | 0,12        | (Max 0,17)        |
| Rated adsorption        | A                 | 0,9         | (Max 1,04)        |
| Lock Rotor Ampere       | A                 | 8,5         |                   |
| Weight                  | Kg / Lbs          | 19 / 42     |                   |
| Air connections         | IN/OUT            | 3/8" BSP    |                   |
| Coolant type            | Freon             | R513A       |                   |

### Standard features

|                    |                        |                        |                      |
|--------------------|------------------------|------------------------|----------------------|
| Control panel:     | Electronic system type | Separator type:        | Demister type        |
| Condenser cooling: | Air cooled             | Compressor type:       | Hermetic type        |
| Ventilator motor:  | Pusher fan             | Installation location: | Indoor               |
| Heat exchanger:    | Aluminium brazed plate | Drain discharge:       | Timed solenoid valve |
| Expansion method:  | Capillary tube         | Electric protection:   | IP 42                |

\* Performances refer to air suction of FAD 20°C (68°F), 1 bar (14.5 psig), and the following operating conditions: 7 bar (100 psig) working pressure, 3°C (37°F) pressure dewpoint, 25°C (77°F) ambient temperature, 35°C (95°F) compressed air inlet temperature.

Performances & specifications: +/- 5%

