



TECHNICAL DATA SHEET

CODE:
01B.360.OBG.0
Rev.00 Pg.1/1
Date 11/05/2015

WATER COOLED AFTERCOOLER

MODEL: A 60 S
Installation method Horizontal

Rated capacity*

Air flow rate	m³/h	360		
	l/min	6000		
	cfm	211,9		
Working pressure - Air side	bar / psi	7,0 / 101,5		(Max 12)
Pressure drop	bar / psi	0,150 / 2,2		
Air inlet temperature	°C / °F	120 / 248		(Max 200 / 392)
Water inlet temperature	°C / °F	15 / 59		(Max 40 / 104)
Air outlet temperature	°C / °F	34 / 93		(Max 66 / 151)
Water consumption	m³/h	0,75		
	l/min	12,50		
	cfm	0,441		
Working pressure - Water side	bar / psi	3,0 / 43,5		(Max 7 / 102)
Air connections	IN	2-1/2" BSP (DN 65)		
	OUT	1-1/2" BSP		
Water connections	IN / OUT	3/4" BSP		
Condensate outlet	G	3/8" BSP		
Dimensions	A	1060 mm	B	37 mm
	A1	157 mm	C	385 mm
	A2	1057 mm	D	89 mm
	L	1355 mm		
Weight	Kg / Lbs	26,5 / 58		

Standard features

Separator type:	Centrifugal	Heat exchanger shell:	Carbon steel
Drain discharge:	Manual, with tap	Condensate Separator:	Aluminium
Heat exchanger tubes:	Stainless steel		

* Performances refer to air suction of FAD 20°C (68°F), 1 bar (14.5 psig)

Performances & specifications: +/- 5%

AI	Air inlet	WI	Water inlet		Condensate outlet
AO	Air outlet	WO	Water outlet		

