



TECHNICAL DATA SHEET

CODE:
01A.A126.VAG.0
Rev.00 Pg.1/1
Date 11/05/2015

WATER COOLED AFTERCOOLER

MODEL:

AV 2100

Installation method

Vertical

Rated capacity*


Air flow rate	m ³ /h	12600		
	l/min	210000		
	cfm	7416,1		
Working pressure - Air side	bar / psi	7,0 / 101,5	(Max 12)	
Pressure drop	bar / psi	0,150 / 2,2		
Air inlet temperature	°C / °F	120 / 248	(Max 120 / 248)	
Water inlet temperature	°C / °F	15 / 59	(Max 40 / 104)	
Air outlet temperature	°C / °F	34 / 93	(Max 66 / 151)	
Water consumption	m ³ /h	27,00		
	l/min	450,00		
	cfm	15,892		
Working pressure - Water side	bar / psi	3,0 / 43,5	(Max 7 / 102)	
Air connections	IN	DN 400		
	OUT	DN 200		
Water connections	IN / OUT	2-1/2" BSP		
Condensate outlet	G	2" BSP		
Dimensions	A	1500 mm	B	340 mm
	A1	150 mm	C	925 mm
	A2	1320 mm	D	406 mm
	E	980 mm	H	2770 mm
Weight	Kg / Lbs	542,5 / 1.196		

Standard features

Separator type:	Centrifugal	Heat exchanger shell:	Carbon steel
Drain discharge:	Manual, with tap	Condensate Separator:	Carbon steel
Heat exchanger tubes:	Copper		

* Performances refer to air suction of FAD 20°C (68°F), 1 bar (14.5 psig)

Performances & specifications: +/- 5%

AI	Air inlet	WI	Water inlet	 Condensate outlet
AO	Air outlet	WO	Water outlet	

