



TECHNICAL DATA SHEET

CODE:
08F.0750.G0.00B0

Rev.03 Pg.1/1
Date 12/01/2021

REFRIGERATED COMPRESSED AIR DRYER

MODEL: DD 750 230/1/50

Rated capacity*

Flow rate	m ³ /h	750	
	l/min	12500	
	cfm	441,4	
Inlet air temperature	°C / °F	35 / 95	(Max 55 / 131)
Outlet air temperature	°C / °F	27 / 81	(Max 47 / 117)
Ambient temperature	°C / °F	25 / 77	(Max 45 / 113)
Working pressure	bar / psi	7,0 / 101,5	(Max 14 / 203)
Pressure drop	bar / psi	0,21 / 3,0	(Max 0,34 / 4,9)
Pressure dew point	°C / °F	7 / 45	
Power supply	V/Ph/Hz	230/1/50	(±10% / -- / ±1)
Rated power consumption	kW	1,23	(Max 1,92)
Rated adsorption	A	5,9	(Max 9,2)
Lock Rotor Ampere	A	33	
Weight	Kg / Lbs	117 / 258	
Air connections	IN/OUT	2" BSP	
Coolant type	Freon	R407C	

Standard features

Control panel:	Electronic system type	Separator type:	Demister type
Condenser cooling:	Air cooled	Compressor type:	Hermetic type
Ventilator motor:	Suction fan	Installation location:	Indoor
Heat exchanger:	Aluminium brazed plate	Drain discharge:	Timed solenoid valve
Expansion method:	Capillary tube	Electric protection:	IP 42

* Performances refer to air suction of FAD 20°C (68°F), 1 bar (14.5 psig), and the following operating conditions: 7 bar (100 psig) working pressure, 7°C (44.5°F) pressure dewpoint, 25°C (77°F) ambient temperature, 35°C (95°F) compressed air inlet temperature.

Performances & specifications: +/- 5%

