



# TECHNICAL DATA SHEET

**CODE:**  
08L.0054AG0.00B0

Rev.5A Pg.1/1  
Date 24/04/2015

## REFRIGERATED COMPRESSED AIR DRYER

**MODEL:** ED 54 230/1/50

Rated capacity\*

Flow rate	m <sup>3</sup> /h	54	
	l/min	900	
	cfm	31,8	
Inlet air temperature	°C / °F	35 / 95	(Max 55 / 131)
Outlet air temperature	°C / °F	27 / 81	(Max 47 / 117)
Ambient temperature	°C / °F	25 / 77	(Max 45 / 113)
Working pressure	bar / psi	7,0 / 101,5	(Max 16 / 232)
Pressure drop	bar / psi	0,07 / 1,02	(Max 0,34 / 4,93)
Pressure dew point	°C / °F	3 / 37	
Power supply	V/Ph/Hz	230/1/50	(±10% / -- / ±1)
Rated power consumption	kW	0,14	(Max 0,22)
Rated adsorption	A	1,07	(Max 1,3)
Lock Rotor Ampere	A	8,9	
Weight	Kg / Lbs	26 / 57	
Air connections	IN/OUT	1/2"BSP	
Coolant type	Freon	R134a	

### Standard features

Control panel:	Electronic system type	Separator type:	Demister type
Condenser cooling:	Air cooled	Compressor type:	Hermetic type
Ventilator motor:	Pusher fan	Installation location:	Indoor
Heat exchanger:	Aluminium brazed plate	Drain discharge:	Timed solenoid valve
Expansion method:	Capillary tube	Electric protection:	IP 42

\* Performances refer to air suction of FAD 20°C (68°F), 1 bar (14.5 psig), and the following operating conditions: 7 bar (100 psig) working pressure, 3°C (37°F) pressure dewpoint, 25°C (77°F) ambient temperature, 35°C (95°F) compressed air inlet temperature.

Performances & specifications: +/- 5%

