



TECHNICAL DATA SHEET

CODE:
08S.1500AG0.00BG
 Rel.03 Pg.1/1
 Date 27/10/2016

REFRIGERATED COMPRESSED AIR DRYER

MODEL: ESD 1500 400/3/50

		Rated capacity*	
Flow rate	m ³ /h	1500	
	l/min	25000	
	cfm	882,9	
Inlet air temperature	°C / °F	35 / 95	(Max 55 / 131)
Outlet air temperature	°C / °F	27 / 81	(Max 47 / 117)
Ambient temperature	°C / °F	25 / 77	(Max 45 / 113)
Working pressure	bar / psi	7,0 / 102	(Max 14 / 203)
Pressure drop	bar / psi	0,16 / 2,3	(Max 0,36 / 5,2)
Pressure dew point	°C / °F	3 / 37	
Power consumption	kW	2,44	(Max 4,93)
Power supply	V/Ph/Hz	400/3/50	(±10% / -- / ±1)
Rated adsorption	A	6,2	(Max 9,54)
Lock Rotor Ampere	A	50	
Weight	Kg / Lbs	244 / 538	
Air connections	IN/OUT	3"	
Coolant type	Freon	R407C	

Standard features

Control panel:	Electronic system type	Separator type:	Demister type
Condenser cooling:	Air cooled	Compressor type:	Hermetic type
Ventilator motor:	Suction fan	Installation location:	Indoor
Heat exchanger:	Aluminum brazed plate	Drain discharge:	Integrated no loss drain
Glycol circulator:	Centrifugal	Electric protection:	IP 42
Expansion method:	Capillary tube		

* Performances refer to air suction of FAD 20°C (68°F), 1 bar (14.5 psig), and the following operating conditions: 7 bar (100 psig) working pressure, 3°C (37°F) pressure dewpoint, 25°C (77°F) ambient temperature, 35°C (95°F) compressed air inlet temperature.

Performances & specifications: +/- 5%

