

REFRIGERATED COMPRESSED AIR DRYER

MODEL:
ESD72 230/1/50
Rated capacity
RATED CAPACITY

m ³ /h	72
l/min	1200
cfm	42

Power supply

V/Ph/Hz 230/1/50

Power consumption

KW 0,32

Full Load cons.

KW 0,44

Rated absorpt.

Ampere 2,03

Full Load Ampere

Ampere 2,58

Lock. Rotor Ampere

Ampere 10,8

Weight

Kg / Lbs 35/77

Air connection

IN/OUT 1/2" BSP

Coolant type

 Freon **R134a**
Inlet air temp.

°C / °F 35 / 95 - (Max 55 / 131)

Outlet air temp.

°C / °F 25 / 77 - (Max 40 / 104)

Ambient temp.

°C / °F 25 / 77 - (Max 45 / 113)

Working pressure

bar / psi 7 / 100 - (Max 16 / 232)

Pressure drop

bar / psi 0,16 / 2,32 - (Max 0,34 / 5)

Pressure dew point

°C / °F 3/37° - ISO CLASS 4

Standard features

Control panel:	Electronic system type
Condenser cooling:	Air cooled
Ventilator motor:	Pusher fan
Heat exchanger:	Aluminium bar & plate, 3-Layers
Expansion method:	Capillary tube
Separator type:	Demister type
Compressor type:	Hermetic type
Glycol circulator:	Centrifugal
Installation location:	Indoor
Drain discharge:	Timed solenoid valve
Electric protection:	IP 42

Performances refer to air suction of FAD 20°C (68°F), 1 bar (1 4.5 psig), and the following operating conditions: 7 bar (100 psig) working pressure, 3°C (37°F) pressure dewpoint, 25° C (77°F) ambient temperature, 35°C (95°F) compressed air inlet temperature.

Performances & specifications: +/- 5%

