

High pressure filters

MODEL

F0130 HDP

Filter capacity	l/min	66667	Flow rates at 40 bar and 20°C QF - Dust Filtration PF - General purpose Protection Filtration HF - High Efficiency Oil Removal Filtration CF - Activated Carbon Filtration
	m³/h	4000	
Working pressure	bar	40 (40 max)	
Air connections	IN/OUT	2" BSP	
Net weight	Kg	7,5	
Standard type of drain	Ball valve		

Filtration grade		QF	PF	HF	CF
Complete filter code		04H.0800.QGA0	04H.0800.PGA0	04H.0800.HGA0	04H.0800.CGA0
Filter element code		04E.0800DQ	04E.0800DP	04E.0800DH	04E.0800DC
Physical filtration process		Interception	Interception+coal escing	Interception+coal escing	Adsorption
Max solid dimension intercepted (ISO 8573-1)	µm	1 µ	1 µ	0,01 µ	//
Max solid dimension intercepted (ISO 8573-1)	Class	3	2	1	//
Remaining oil content after filtration (ISO 12500-1)	mg/m³	//	0,6 mg/m³	0,01 mg/m³	0,003 mg/m³
Remaining oil content after filtration (ISO 12500-1)	Class	//	2	1	//
Max temperature	°C	80	80	80	30
Pressure drop with new element	bar	0,05	0,1	0,1	0,08
Pressure drop with saturated elements	bar	0,4	0,4	0,4	0,4
Element replacement time	hours	4000 h	4000 h	4000 h	1000 h
Element replacement time	months	6	6	6	3

Line pressure [bar]	7	10	13	16	20	24	28	32	36	40
Correction factor	0,20	0,27	0,35	0,42	0,52	0,61	0,71	0,81	0,90	1,00

Dimensions (mm)	
A	705
B	170
C	52
D	170

