

High pressure filters

MODEL

F0220 HDP

Filter capacity	l/min	108333	Flow rates at 40 bar and 20°C QF - Dust Filtration PF - General purpose Protection Filtration HF - High Efficiency Oil Removal Filtration CF - Activated Carbon Filtration
	m³/h	6500	
Working pressure	bar	40 (40 max)	
Air connections	IN/OUT	2½ BSP	
Net weight	Kg	12,2	
Standard type of drain	Ball valve		

Filtration grade		QF	PF	HF	CF
Complete filter code		04H.1300.QGA0	04H.1300.PGA0	04H.1300.HGA0	04H.1300.CGA0
Filter element code		04E.1300DQ	04E.1300DP	04E.1300DH	04E.1300DC
Physical filtration process		Interception	Interception+coal escing	Interception+coal escing	Adsorption
Max solid dimension intercepted (ISO 8573-1)	µm	1 µ	1 µ	0,01 µ	//
Max solid dimension intercepted (ISO 8573-1)	Class	3	2	1	//
Remaining oil content after filtration (ISO 12500-1)	mg/m³	//	0,6 mg/m³	0,01 mg/m³	0,003 mg/m³
Remaining oil content after filtration (ISO 12500-1)	Class	//	2	1	//
Max temperature	°C	80	80	80	30
Pressure drop with new element	bar	0,05	0,1	0,1	0,08
Pressure drop with saturated elements	bar	0,4	0,4	0,4	0,4
Element replacement time	hours	4000 h	4000 h	4000 h	1000 h
Element replacement time	months	6	6	6	3

Line pressure [bar]	7	10	13	16	20	24	28	32	36	40
Correction factor	0,20	0,27	0,35	0,42	0,52	0,61	0,71	0,81	0,90	1,00

Dimensions (mm)	
A	755
B	200
C	68
D	170

