

High pressure filters

MODEL

F0330 HDP

Filter capacity	l/min	16667	Flow rates at 40 bar and 20°C QF - Dust Filtration PF - General purpose Protection Filtration HF - High Efficiency Oil Removal Filtration CF - Activated Carbon Filtration
	m ³ /h	10000	
Working pressure	bar	40 (40 max)	
Air connections	IN/OUT	3" BSP	
Net weight	Kg	15,7	
Standard type of drain	Ball valve		

Filtration grade		QF	PF	HF	CF
Complete filter code		04H.2000.QGA0	04H.2000.PGA0	04H.2000.HGA0	04H.2000.CGA0
Filter element code		04E.2000DQ	04E.2000DP	04E.2000DH	04E.2000DC
Physical filtration process		Interception	Interception+coal escing	Interception+coal escing	Adsorption
Max solid dimension intercepted (ISO 8573-1)	µm	1 µ	1 µ	0,01 µ	//
Max solid dimension intercepted (ISO 8573-1)	Class	3	2	1	//
Remaining oil content after filtration (ISO 12500-1)	mg/m ³	//	0,6 mg/m ³	0,01 mg/m ³	0,003 mg/m ³
Remaining oil content after filtration (ISO 12500-1)	Class	//	2	1	//
Max temperature	°C	80	80	80	30
Pressure drop with new element	bar	0,05	0,1	0,1	0,08
Pressure drop with saturated elements	bar	0,4	0,4	0,4	0,4
Element replacement time	hours	4000 h	4000 h	4000 h	1000 h
Element replacement time	months	6	6	6	3

Line pressure [bar]	7	10	13	16	20	24	28	32	36	40
Correction factor	0,20	0,27	0,35	0,42	0,52	0,61	0,71	0,81	0,90	1,00

Dimensions (mm)	
A	1035
B	200
C	68
D	170

