



TECHNICAL DATA SHEET

ST 08U.3300BGA0

Rev. 00 Pag. 1/1

Date 28/02/2011

DESICCANT DRYER

MODEL

HL3300PRO-70C

TYPE

HEATLESS REGENERATION

OPERATING DATA

APPLICATION FLUID		AIR
NOMINAL CAPACITY	l/min	44000
	m ³ /h	2640
NOMINAL CONDITIONS	cfm	1554
PRESSURE RATE	bar	7
INLET AIR TEMPERATURE RATE	°C	35
PRESSURE DEW POINT	°C	- 70
RELATIVE HUMIDITY INLET AIR	%	100
PRESSURE DROP	bar	0,128
TYPICAL DRYING CYCLE COMPLETE	min	5
TYPICAL DRYING TIME FOR ONE COLUMN	min	2,5
REGENERATION AIR CONSUMPTION (NOMINAL FLOW RATE)	%	15

Without Energy Management System (EMS)

OPERATING LIMITS

MINIMUM WORKING PRESSURE	bar	5
MAXIMUM WORKING PRESSURE	bar	10
MAXIMUM INLET AIR TEMPERATURE	°C	50
MINIMUM AMBIENT TEMPERATURE	°C	1
MAXIMUM AMBIENT TEMPERATURE	°C	50

GENERAL DATA

AIR CONNECTION	IN/OUT	DN125	ISO 7/1
POWER SUPPLY	V/Ph/Hz	230/1/50	
DESICCANT MEDIUM		Alumina + Molecular Sieve	
ELECTRICAL PROTECTION		IP 54	
WEIGHT	kg	1773	

DIMENSION

HEIGHT (A)	mm	2329
WIDTH (B)	mm	2150
DEPTH (C)	mm	1592

