

REFRIGERATED COMPRESSED AIR DRYER

MODEL: **HTD 35 230/1/50**

Rated capacity*

Flow rate	m ³ /h	35		
	l/min	583		
	cfm	20,6		
Inlet air temperature	°C / °F	60 / 140		(Max 82 / 180)
Outlet air temperature	°C / °F	27 / 81		(Max 47 / 117)
Ambient temperature	°C / °F	25 / 77		(Max 45 / 113)
Working pressure	bar / psi	7,0 / 101,5		(Max 16 / 232)
Pressure drop	bar / psi	0,08 / 1,16		(Max 0,34 / 4,93)
Pressure dew point	°C / °F	7 / 45		
Power supply	V/Ph/Hz	230/1/50		(±10% / -- / ±1)
Rated power consumption	kW	0,16		(Max 0,22)
Rated adsorption	A	1,07		(Max 1,3)
Lock Rotor Ampere	A	8,9		
Weight	Kg / Lbs	32 / 71		
Air connections	IN/OUT	½" BSP		
Coolant type	Freon	R134a		

Standard features

Control panel:	Electronic system type	Separator type:	Demister type
Condenser cooling:	Air cooled	Compressor type:	Hermetic type
Ventilator motor:	Suction fan	Installation location:	Indoor
Heat exchanger:	Aluminium brazed plate	Drain discharge:	Timed solenoid valve
Expansion method:	Capillary tube	Electric protection:	IP 42

* Performances refer to air suction of FAD 20°C (68°F), 1 bar (14.5 psig), and the following operating conditions: 7 bar (100 psig) working pressure, 3°C (37°F) pressure dewpoint, 25°C (77°F) ambient temperature, 60°C (140°F) compressed air inlet temperature.

Performances & specifications: +/- 5%

